



"RUPI CABLE- AND WIRE STOCKINGS,
SIMPLY BRILLIANT AND INDISPENSABLE"

RUPI-COLOGNE®, GMBH

YOUR SPECIALIST AROUND CABLE AND WIRE

Cable and rope stockings

>> RP- 100



These stockings provide a strong and reliable tensile connection when they are fixed to the cable, rope or pipe front end. When routing through cable channels, open trenches, on trays or other installations – this mesh of galvanized steel strands, closed on one side and fitted with a respective clamp and thimble, have a special arrangement of the mesh sizes (relative to the respective diameter) ensure a high flexibility and adhesion on the material to be inserted and thereby an unproblematic insertion.



(2-layered / standard)



(3-layered / enhanced)

RP-100:

Available in standard lengths 1250 mm, 1500 mm and 2000 mm. Other lengths upon request!
Also available in the following design:

>> **STAINLESS STEEL (STAINLESS STEEL BRAIDING)**

>> **STRAINED BOWDEN CABLE**

>> **STAINLESS STEEL REINFORCED** (three-layer design for higher tensile strength)

>> **PLASTIC COATED STRANDS**



rupi-Cologne, GmbH

Industriestr. 30-32
„Einfahrt Siemensstraße“
67269 Grünstadt
Germany

Phone + Fax

+49(0)2234-95395- 0
+49(0)2234-95395- 22

E-mail + Web

info@rupi-cologne.de
www.rupi-cologne.de



rupi Köln seit 1966

"RUPI CABLE- AND WIRE STOCKINGS,
SIMPLY BRILLIANT AND INDISPENSABLE"

RUPI-COLOGNE® GMBH

YOUR SPECIALIST AROUND CABLE AND WIRE

Cable and rope stockings

>> RP- 100

For cables and ropes with \varnothing from - to	Permissible tension load in kN / tons approx.	Thimble size for bolt \varnothing approx. mm	Part number <small>Please indicate required length/s (e.g. RP- 110-1500) for stocking length 1500</small>
08 - 15 mm	5,12 / 0,52	13	RP - 110 - + length
15 - 20 mm	6,93 / 0,71	15	RP - 115 - + length
20 - 30 mm	8,67 / 0,88	15	RP - 120 - + length
30 - 40 mm	10,40 / 1,06	16	RP - 130 - + length
40 - 50 mm	21,36 / 2,18	20	RP - 140 - + length
50 - 60 mm	21,36 / 2,18	20	RP - 150 - + length
60 - 80 mm	28,48 / 2,90	20	RP - 160 - + length
80 - 100 mm	45,60 / 4,65	26	RP - 180 - + length
100 - 120 mm	50,67 / 5,17	26	RP - 1100 - + length
120 - 160 mm	85,12 / 8,68	flexible rope eyelets	RP - 1120 - + length
140 - 190 mm	99,31 / 10,13	flexible rope eyelets	RP - 1140 - + length
180 - 250 mm	127,68 / 13,02	flexible rope eyelets	RP - 1180 - + length
220 - 320 mm	156,05 / 15,91	flexible rope eyelets	RP - 1220 - + length
280 - 450 mm	198,61 / 20,25	flexible rope eyelets	RP - 1280 - + length



**Greater loads and higher tensile forces
and special designs on request.
Produceable immediately.**

rupi-Cologne, GmbH

Industriestr. 30-32
„Einfahrt Siemensstraße“
67269 Grünstadt
Germany

Phone + Fax

+49(0)2234-95395- 0
+49(0)2234-95395- 22

E-mail + Web

info@rupi-cologne.de
www.rupi-cologne.de