


## Cable and rope twin eye stockings

### >> RP- 200



Attached at any point of a cable, rope or pipe, these stockings can be safely pulled over with a pull rope.

Whether pulling in cable channels, open trenches, on trays or any other installations, this mesh made of galvanized steel in a weave open at both ends is fitted with the respective clamps and thimbles can be used to pull in the cable etc. as required. Of course, the proper mesh size guarantees a high flexibility and adhesion.



(2-layered / standard)



(3-layered / enhanced)

#### **RP-200:**

Available in standard lengths 1250 mm, 1500 mm and 2000 mm. Other lengths upon request!  
Also available in the following design:

>> **STAINLESS STEEL (STAINLESS STEEL BRAIDING)**

>> **STRAINED BOWDEN CABLE**

>> **STAINLESS STEEL REINFORCED** (three-layer design for higher tensile strength)

>> **PLASTIC COATED STRANDS**



**rupi-Cologne, GmbH**

Industriestr. 30-32  
„Einfahrt Siemensstraße“  
67269 Grünstadt  
Germany

**Phone + Fax**

+49(0)2234-95395- 0  
+49(0)2234-95395- 22

**E-mail + Web**

info@rupi-cologne.de  
www.rupi-cologne.de



"RUPI CABLE- AND WIRE STOCKINGS,  
SIMPLY BRILLIANT AND INDISPENSABLE"

**RUPI-COLOGNE® GMBH**

**YOUR SPECIALIST AROUND CABLE AND WIRE**

## Cable and rope twin eye stockings

### >> RP- 200

For cables and ropes with $\varnothing$ from - to	Permissible tension load in kN / tons approx.	Thimble size for bolt $\varnothing$ approx. mm	Part number <small>Please indicate required length/s (e.g. RP- 210-1500) for stocking length 1500</small>
08 - 15 mm	5,12 / 0,52	13	RP - 210 - + length
15 - 20 mm	6,93 / 0,71	15	RP - 215 - + length
20 - 30 mm	8,67 / 0,88	15	RP - 220 - + length
30 - 40 mm	10,40 / 1,06	16	RP - 230 - + length
40 - 50 mm	21,36 / 2,18	20	RP - 240 - + length
50 - 60 mm	21,36 / 2,18	20	RP - 250 - + length
60 - 80 mm	28,48 / 2,90	20	RP - 260 - + length
80 - 100 mm	45,60 / 4,65	26	RP - 280 - + length
100 - 120 mm	50,67 / 5,17	26	RP - 2100 - + length
120 - 160 mm	85,12 / 8,68	flexible rope eyelets	RP - 2120 - + length
140 - 190 mm	99,31 / 10,13	flexible rope eyelets	RP - 2140 - + length
180 - 250 mm	127,68 / 13,02	flexible rope eyelets	RP - 2180 - + length
220 - 320 mm	156,05 / 15,91	flexible rope eyelets	RP - 2220 - + length
280 - 450 mm	198,61 / 20,25	flexible rope eyelets	RP - 2280 - + length



**Greater loads and higher tensile forces  
and special designs on request.  
Produceable immediately.**

#### rupi-Cologne, GmbH

Industriestr. 30-32  
„Einfahrt Siemensstraße“  
67269 Grünstadt  
Germany

#### Phone + Fax

+49(0)2234-95395- 0  
+49(0)2234-95395- 22

#### E-mail + Web

info@rupi-cologne.de  
www.rupi-cologne.de