


Cable and rope twin eye lace up stockings

>> RP- 300



Cable stockings with two thimbles or eyelets attached by compression are available in a version with both ends open or in an open weave with one side completely open. These are used for pulling and transporting any kind of heavy cables or pipes.

The stockings open at both ends have the advantage against the ones open at only one end that the cable or pipe can extend beyond the stocking at either end between the eyes or thimbles. The stockings that open on the side can be placed on any position over a pipe or cable and then be laced up and tightened using two strand ties.



(2-layered / standard)



(3-layered / enhanced)

RP-300:

Available in standard lengths 1250 mm, 1500 mm and 2000 mm. Other lengths upon request!
Also available in the following design:

>> **STAINLESS STEEL (STAINLESS STEEL BRAIDING)**

>> **STRAINED BOWDEN CABLE**

>> **STAINLESS STEEL REINFORCED** (three-layer design for higher tensile strength)

>> **PLASTIC COATED STRANDS**





"RUPI CABLE- AND WIRE STOCKINGS,
SIMPLY BRILLIANT AND INDISPENSABLE"

RUPI-COLOGNE[®] GMBH

YOUR SPECIALIST AROUND CABLE AND WIRE

Cable and rope twin eye lace up stockings

>> RP- 300

For cables and ropes with \varnothing from - to	Permissible tension load in kN / tons approx.	Thimble size for bolt \varnothing approx. mm	Part number <small>Please indicate required length/s (e.g. RP- 310-1500) for stocking length 1500</small>
08 - 15 mm	5,12 / 0,52	flexible rope eyelets	RP - 310 - + length
15 - 20 mm	6,93 / 0,71	flexible rope eyelets	RP - 315 - + length
20 - 30 mm	8,67 / 0,88	flexible rope eyelets	RP - 320 - + length
30 - 40 mm	10,40 / 1,06	flexible rope eyelets	RP - 330 - + length
40 - 50 mm	21,36 / 2,18	flexible rope eyelets	RP - 340 - + length
50 - 60 mm	21,36 / 2,18	flexible rope eyelets	RP - 350 - + length
60 - 80 mm	28,48 / 2,90	flexible rope eyelets	RP - 360 - + length
80 - 100 mm	45,60 / 4,65	flexible rope eyelets	RP - 380 - + length
100 - 120 mm	50,67 / 5,17	flexible rope eyelets	RP - 3100 - + length
120 - 160 mm	85,12 / 8,68	flexible rope eyelets	RP - 3120 - + length
140 - 190 mm	99,31 / 10,13	flexible rope eyelets	RP - 3140 - + length
180 - 250 mm	127,68 / 13,02	flexible rope eyelets	RP - 3180 - + length
220 - 320 mm	156,05 / 15,91	flexible rope eyelets	RP - 3220 - + length
280 - 450 mm	198,61 / 20,25	flexible rope eyelets	RP - 3280 - + length



**Greater loads and higher tensile forces
and special designs on request.
Produceable immediately.**

rupi-Cologne, GmbH

Industriestr. 30-32
„Einfahrt Siemensstraße“
67269 Grünstadt
Germany

Phone + Fax

+49(0)2234-95395- 0
+49(0)2234-95395- 22

E-mail + Web

info@rupi-cologne.de
www.rupi-cologne.de